## RU2335852

## FEDERAL INSTITUTE OF INDUSTRIAL PROPERTY

Selected
databases
Query
parameters
Query
definition
Refine query
Query results
Basket
Saved queries
Statistics
Help
Proposals
Exit

Document: PDF

Status of 19.01.2009 - operates

(11) Number of 2335852

the patent document

(13) Kind of **C2** 

document

(14) Document 2008.10.10

date

(19) Publishing RU

country or organization

(21) 2005115862/09

Application number registered

(22) 2003.10.24

Application filing date

(30) Priority 60/421,309 2002.10.25 US

data

(24) Date 2003.10.24

started of validity of the patent

(43) 2006.01.20

Unexamined printed documents without grant

(45) Date 2008.10.10

(51) Main **H04L1/00** (2006.01)

classification

**IPC** 

Title WIRELESS LOCAL AREA NETWORK SYSTEM

WITH MULTIPLE INPUTS AND MULTIPLE

**OUTPUTS** 

(56) List of WO 02078211 A, 03.10.2002. RU 2141168 C1, 10.11.1999. prior art US 6452981 B1, 17.09.2002. WO 0176110 A, 11.10.2001.

documents

(72) Inventor UOLTON Dzh. Rodni (US)

information

(72) Inventor UOLLEhJS Mark S. (US)

information

(72) Inventor KETChUM Dzhon U. (US)

information

(72) Inventor GOVARD Stiven Dzh. (US)

information

(73) Grantee KVEhLKOMM INKORPOREJTED (US)

(asignee) information

(85) PCT date 2005.05.25

art. 22/39

(86) PCT or US 03/34514 (24.10.2003)

regional filing information

(87) PCT or WO 2004/039011 (06.05.2004)

regional filing information (publ.)

Mail address 129090, Moskva, ul. B.Spasskaja, 25, str.3, OOO

"Juridicheskaja firma Gorodisskij i Partnery", pat.pov.

Ju.D.Kuznetsovu, reg.№ 595

## #2335852. Abstract

FIELD: information technology.

SUBSTANCE: system uses channel structure with several configurable transport channels. The system supports multiple data transmission speed values and modes, which can be configured on the basis of channel conditions and user terminal perfromance level. The system also uses pilot structures with several pilot signal type, for instance, beacon

(MIMO), controlled template and carrier pilot signal) for different functions, implements transmission speed, synchronisation and power control circuits to provide appropriate system operation, and uses random access for system access by user terminals, fast acknowledgement and quick resource assignment. To compensate for differences in frequency response of transmission/receiving circuits, calibration can be performed in access point and user terminals. Three-dimensional processing can be facilitated using advantages of downstream and upstream lines, as well as calibration.

EFFECT: increase of transmission bandwidth capacity.

18 cl, 33 dwg, 36 tbl

